


Brass/Steel

Nominal Diameter

5 = 20 mm²



Rectus Series

21

Low Pressure



Technical Description

Mini industrial coupling with the world's most popular profile in this nominal diameter. Above average flow performance for liquid and gaseous media. Coupling system with single-hand operation. Small dimensions and large band width in materials and valve variants.

Dust Protections (P. 319)
for Coupling Part.-No. SK16S

Working Temperature*
-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

<p>Working Pressure** 35 bar ** maximum static working pressure with safety factor 4 to 1.</p>	<p>35 bar</p>	<p>8 bar</p>
<p>Features</p> <ul style="list-style-type: none"> • Minimal, almost imperceptible leakage when uncoupling • No air locked into the system during the coupling process 		
<p>Material Coupling: Brass Plug: Brass Seals: NBR</p>		
<p>Interchangeability</p> <ul style="list-style-type: none"> • Rectus 90 • Camozzi • Ewo • Kani 		
<p>Flow diagrams</p>		
<p>Air</p>	<p>Air</p>	<p>Air</p>
<p>Water</p>	<p>Water</p>	<p>Water</p>